

RECEIVED
CENTRAL FAX CENTER

OCT 24 2006

IN THE CLAIMS

1. (Original) A method comprising:
 - computing an energy delay² product metric for a current architecture configuration over a predetermined period of time;
 - comparing the computed energy delay² product metric to an energy delay² product metric of a prior architecture configuration to determine an energy effectiveness of the current architecture configuration; and
 - adjusting a number of active instruction schedulers of the current architecture configuration according to the energy effectiveness of the current architecture configuration.
2. (Original) The method of claim 1, wherein computing the energy delay² product metric comprises:
 - selecting an active instruction scheduler from one or more active instruction schedulers of the current architecture configuration matching a selected instruction scheduler type;
 - computing an energy consumption value for the selected instruction scheduler and one or more associated logic elements as a product of an access count and a predetermined energy per access amount of the selected instruction scheduler and the predetermined period of the time squared;
 - repeating selecting of the instruction scheduler, computing of the energy consumption value and storing of the energy consumption value for each instruction scheduler of the current architecture configuration matching the selected instruction scheduler type to form an energy consumption sum;
 - storing the energy consumption product sum for the instruction selected scheduler type; and
 - repeating the selecting the active instruction scheduler, computing of the energy consumption product, repeating, and storing the energy consumption product for each instruction scheduler type of the current architecture configuration to form the energy consumption value of the current architecture configuration.

3. (Original) The method of claim 1, wherein comparing the computed energy delay² product value comprises:

selecting an instruction scheduler type of the current architecture configuration;

determining a computed energy consumption product for the selected instruction scheduler type;

comparing the computed energy delay² product of the selected instruction scheduler type to a previously computed energy delay² product value;

identifying a decrease in the effectiveness of the current architecture configuration if the computed energy delay² product is less than the previously computed energy consumption product; and

identifying an increase in the effectiveness of the current architecture configuration if the computed energy delay² product is greater than the previously computed energy delay² product.

4. (Original) The method of claim 1, wherein adjusting comprises:

identifying an increase in the effectiveness of the current architecture configuration;

identifying a direction indicator state for an instruction scheduler type of the current architecture configuration as one of an increased state and a decreased state;

increasing the number of active instruction schedulers for the current architecture configuration if the direction indicator is in an increased state;

reducing the number of active instruction schedulers for the current architecture configuration if the direction indicator is in a decreased state; and

maintaining a state of the direction indicator for the selected instruction scheduler type.

5. (Original) The method of claim 1, wherein adjusting comprises:

identifying a decrease in the effectiveness of the current architecture configuration;

identifying a direction indicator state for an instruction scheduler type of the current architecture configuration as one of an increased state and a decreased state;

reducing the number of active instruction schedulers for the current architecture configuration if the direction indicator is in an increased state;

increasing the number of active instruction schedulers for the current architecture configuration if the direction indicator is in a decreased state; and
switching a state of the direction indicator for the selected instruction scheduler type.

6. (Original) The method of claim 5, wherein increasing the number of active instruction schedulers comprises:

selecting a disabled instruction scheduler of the current architecture configuration; and
enabling a clock input to the instruction scheduler and one or more associated functional blocks.

7. (Previously Presented) The method of claim 5, wherein decreasing the number of active instruction schedulers comprises:

selecting an active instruction scheduler of the current architecture configuration; and
disabling a clock input to the instruction scheduler and one or more associated functional units.

8. (Original) The method of claim 1, further comprising:

executing an adjusted architecture configuration over a predetermined interval;
computing an energy delay² product for the adjusted architecture configuration consumed during execution over the predetermined interval;

computing an energy delay² product for an increased architecture configuration having one or more additional active instruction schedulers than the adjusted configuration architecture consumed during execution over a reduced time interval;

computing an energy delay² product consumed by a decreased architecture configuration having a reduced number of active instruction schedulers than the adjusted configuration architecture consumed during over the reduced interval of time;

normalizing the computed energy delay² products for the increased and decreased architecture configurations;

identifying an architecture configuration having a lowest energy delay² product; and

selecting the identified architecture configuration as a current architecture configuration.

9. (Original) The method of claim 8, further comprising:
detecting one of the increased architecture configuration or decreased architecture configuration as having the lowest energy.delay² product;
performing the method of claim 8 with the detected architecture configuration as the adjusted architecture configuration.
10. (Original) The method of claim 2, wherein computing the energy consumption value comprises:
calculating an energy consumption value for one or more functional units associated with the selected instruction scheduler;
calculating an energy consumption value for a register file associated with the selected instruction scheduler;
calculating an energy consumption value for each component the selected instruction scheduler;
summing the energy consumption values of the instruction scheduler, functional units and register file; and
computing the energy delay² product as a product of the energy consumption sum and a square of the predetermined time interval.
11. (Currently Amended) An article of manufacture including a machine readable storage medium having stored thereon instructions which may be used to program a system to perform a method, comprising:
computing an energy delay² product value for a current architecture configuration over a predetermined period of time;
comparing the computed energy delay² product value to an energy consumption value of a prior architecture configuration to determine an energy effectiveness of the current architecture configuration; and
adjusting a number of active instruction schedulers of the current architecture configuration according to the energy effectiveness of the current architecture configuration.

12. (Original) The article of manufacture of claim 11, wherein computing the delay² product value comprises:

selecting an active instruction scheduler from one or more active instruction schedulers of the current architecture configuration matching a selected instruction scheduler type;

computing an energy consumption value for the selected instruction scheduler and one or more associated logic elements as a product of an access count and a predetermined energy per access amount of the selected instruction scheduler and the predetermined period of the time squared;

repeating selecting of the instruction scheduler, computing of the energy consumption value and storing of the energy consumption value for each instruction scheduler of the current architecture configuration matching the selected instruction scheduler type to form an energy consumption sum;

storing the energy consumption product sum for the instruction selected scheduler type; and

repeating the selecting the active instruction scheduler, computing of the energy consumption value, repeating, and storing the energy consumption value for each instruction scheduler type of the current architecture configuration to form the energy consumption value of the current architecture configuration.

13. (Original) The article of manufacture of claim 11, wherein comparing the computed energy delay² product value comprises:

selecting an instruction scheduler type of the current architecture configuration;

determining a computed energy delay² product for the selected instruction scheduler type;

comparing the computed energy delay² product of the selected instruction scheduler type to a previously computed energy consumption product value;

identifying a decrease in the effectiveness of the current architecture configuration if the computed energy delay² product is less than the previously computed energy delay² product; and

identifying an increase in the effectiveness of the current architecture configuration if the computed energy delay² product is greater than the previously computed energy delay² product.

14. (Original) The article of manufacture of claim 11, wherein adjusting comprises:
identifying an increase in the effectiveness of the current architecture configuration;
identifying a direction indicator state for an instruction scheduler type of the current architecture configuration as one of an increased state and a decreased state;
increasing the number of active instruction schedulers for the current architecture configuration if the direction indicator is in an increased state;
reducing the number of active instruction schedulers for the current architecture configuration if the direction indicator is in a decreased state; and
maintaining a state of the direction indicator for the selected instruction scheduler type.

15-17. (Cancelled)

18. (Original) The article of manufacture of claim 11, further comprising:
executing an adjusted architecture configuration over a predetermined interval;
computing an energy delay² product for the adjusted architecture configuration consumed during execution over the predetermined interval;
computing an energy delay² product for an increased architecture configuration having one or more additional active instruction schedulers than the adjusted configuration architecture consumed during execution over a reduced time interval;
computing an energy delay² product consumed by a decreased architecture configuration having a reduced number of active instruction schedulers than the adjusted configuration architecture consumed during over the reduced interval of time;
normalizing the computed energy delay² products for the increased and decreased architecture configurations;
identifying an architecture configuration having a lowest energy delay² product; and
selecting the identified architecture configuration as a current architecture configuration.

19. (Original) The article of manufacture of claim 18, further comprising:
detecting one of the increased architecture configuration or decreased architecture configuration as having the lowest energy delay² product;
performing the method of claim 18 with the detected architecture configuration as the adjusted architecture configuration.

20. (Original) The article of manufacture of claim 12, wherein computing the energy delay² product comprises:

calculating an energy consumption value for one or more functional units associated with the selected instruction scheduler;

calculating an energy consumption value for a register file associated with the selected instruction scheduler;

calculating an energy consumption value for each component of the selected instruction scheduler;

summing the energy consumption values of the instruction scheduler, functional units and the register file; and

computing the energy delay² product as a product of the energy consumption sum and a square of the predetermined time interval.

21-30. (Cancelled)